


# SWAGE™ Dissolvable Frac Plug



The SWAGE™ Dissolvable Frac Plug utilizes high strength dissolvable components to provide a dependable, durable and cost-effective design for temporary zone isolation during stage fracs in both horizontal and vertical wells. SWAGE™ dissolvable frac plugs are constructed of 100% dissolvable material and do not utilize an element or traditional slip system. TEAM's patented SWAGE™ frac plug utilizes a patented grit slip system that enable the plug to function without the traditional element and slip system.

SWAGE™ frac plugs are run on industry standard electric line setting tools. Wireline adapter kits exist for each of these setting tools and have been optimized to increase flow area through the kit to maximize run in speed.

## FEATURES AND BENEFITS

- Rated to 10,000 psi at temperatures ranging from 100 to 350F
- Constructed of 100% dissolvable material
- Fully dissolves in a short period of time
- Sets securely in any casing grade
- Patented grit-slip anchors securely in any casing grade
- Plug length less than 10 in.
- Large ID bore for increased flow-back after frac
- Available in various material combinations for all temperature ranges

### SWAGE™ DISSOLVABLE FRAC PLUG

CASING SIZE Inches	CASING WEIGHT lbs/ft	TOOL O.D. Inches	RIH LENGTH Inches	AS-SET LENGTH	AS-SET SEAT ID	BALL SIZE Inches	ADAPTER KIT OD
5.500	17.0	4.702	10.25	8.00	2.00	2.75	4.140
5.500	20.0	4.588	10.25	8.00	2.00	2.75	4.140
5.500	23.0	4.480	10.25	8.00	2.00	2.75	4.140
5.500	26.0	4.310	10.25	8.00	2.00	2.75	4.140
4.500	11.6	3.810	6.65	5.00	1.70	2.25	3.405
4.500	13.5	3.730	6.65	5.00	1.70	2.25	3.405
4.500	15.1	3.600	6.65	5.00	1.70	2.25	3.405

